ESS1508C

8 HDDs eSATA Storage

Features

> ESS1508C: 2U standard 19-inch rack case
> Connect master device via eSATA or USB
> eSATA port transmission speed up to 3Gbps
> USB 3.0 port data transmission higher than normal
> Powerful R / W performance: read >64MB/s, write >64MB/s
> ESS1508C: Max support Internal 8 SATA HDD up to 48TB
> Recommended with DVR, NVR connection

ESS1508C

Technical Specifications

Model	ESS1508C
Specification	
eSATA Interface	1 port, up to 3Gbps
USB Interface	1 port, USB 3.0
Internal HDD	8 SATA ports
R/W Performance	Read >64MB/s, Write >64MB/s
Connection Device	DVR, NVR
General	
Power Supply	AC 100~240V, 50/60Hz
Power Consumption (without HDD)	9.8W
Fan	1 pcs
Working Environment	0℃~40℃（Working），-20℃~70℃(Storage) 86kpa～106kpa /10%—90%RH(working), 5%-90%RH(Storage)
Dimension(WxHxD)	2U, 440mmx89mmx448mm
Weight	6.5KG

Belco Security Sdn Bhd
No.14 Jalan Intan 1,
Taman Puchong Intan,
47150 Puchong, Selangor, Malaysia.
Email: sales@belco.com.my
www.belco.com.my

*Design and specifications are subject to change without notice.

© 2016 Belco Security Sdn Bhd