

SPECTRA Keypads
LED



K32+
Wired LED Keypad

- Features
 - Controls and displays up to 32 zones in 2 partitions
 - 7 one-touch action buttons
 - 3 keypad-activated panic alarms
 - StayD™ mode
 - Independently-set chime zones
 - Separate Arm, Sleep, Stay, and Off LEDs per partition
 - Available in multiple languages
 - In-field firmware upgradeable via 307USB

► Specifications

Input Voltage	12 to 14 Vdc
Current Consumption	Typical: 40mA Maximum: 150mA
Keypad Zone Input	1
Operating Temperature	-10 to 55 °C (14 to 131 °F)
Dimensions	12.6 x 15 x 2.7 cm (5 x 5.9 x 1.1 in.)



K636
Wired LED Keypad

- Features
 - Controls and displays up to 10 zones; partition 1 only
 - StayD™ Status LED
 - Arm, Sleep, Stay and Off keys illuminate to indicate partition status
 - Patented Key Light display (button lights up to indicate an open zone)
 - Adjustable key backlight
 - Available in multiple languages

► Specifications

Input Voltage	12 to 14 Vdc
Current Consumption	Minimum: 15mA Maximum: 30mA
PGM Output	1 (follows arm status)
Operating Temperature	0 to 50 °C (32 to 122 °F)
Dimensions	14.3 x 7.8 x 2.3 cm (5.6 x 3.1 x 0.9 in.)



K10V / K10H
Wired LED Keypad

- Features
 - Controls and displays up to 10 zones in 2 partitions
 - 7 one-touch action buttons
 - 3 keypad-activated panic alarms
 - StayD™ mode
 - 10-zone LED display
 - LED displays for each partition: Arm, Sleep, Stay and Off
 - Patented Key Light display (button lights up to indicate an open zone)
 - Adjustable key backlight
 - Connects to 4-wire communication bus
 - Available in multiple languages

► Specifications

Input Voltage	12 to 14 Vdc
Current Consumption	Typical: 18mA Maximum: 73mA
Keypad Zone Input	1
Operating Temperature	-10 to 55 °C (14 to 131 °F)
Dimensions	K10H: 9.6 x 13.5 x 3.2 cm (3.8 x 5.3 x 1.3 in) K10V: 13.5 x 9.6 x 3.2 cm (5.3 x 3.8 x 1.3 in)



SPECTRA Zone Expanders



ZX8SP
8-Zone Expansion Module

- Features
 - 8 zone inputs
 - 1 PGM output (50 mA PGM)
 - Uses zone input as an anti-tamper switch input

► Specifications

Input Voltage	12 to 16 Vdc
Current Consumption	28 mA
Operating Temperature	-20 to 50 °C (-4 to 122 °F)
Dimensions	14 x 4.5 x 1.8 cm (5.5 x 1.8 x 0.7 in.)

