



THE RIGHT BATTERY FOR YOUR SURVEILLANCE DEVICE

- › Powerful Battery Day After Day
- › Reliable For Every Generation



Rechargeable



Highly Efficient



Leak Proof



Maintenance FREE

Specifications:-

Nominal Voltage		12V
Capacity (20HR, 25°C)		7.0Ah
Dimension	Length	150mm (5.94inch)
	Width	65mm (2.56inch)
	Height	94mm (3.70inch)
	Total Height	100mm (3.94inch)
Approx. Weight		2.15kg (4.9lbs)
Internal resistance (Fully charged, 25°C)		Approx. 28m Ω
Capacity	40°C	102%
effected by	25°C	100%
temperature	0°C	85%
(20HR)	-15°C	65%
Self-discharge (25°C)	3 month	Remaining Capacity : 91%
	6 month	Remaining Capacity : 82%
	12 month	Remaining Capacity : 65%
Nominal operating temperature		25°C ± 3°C (77°F ± 5°F)
Float charging voltage (25°C)		13.60 to 13.80V
Cyclic charging voltage (25°C)		14.50 to 14.90V
Maximum charging current		2.1A
Terminal material		Copper
Maximum discharge current		105A (5 sec)

Safety & Compliance

BELCO believes that, only by consistently supplying high quality products that serve your needs can we build a trustworthy and long-term relationship with you. To ensure the quality of this battery, it has attained the following certificate :

Quality Management System (ISO9001 ISO14001 OHSAS18001)

Made in Indonesia