

SMART NET CLAIRE SNC-A SERIES

1500VA - 3000VA

Features

- Low Frequency Design With Best Stability
- Pure Sine Wave Output
- Automatic Voltage Regulation (AVR)
- User-Friendly LCD Display
- Cold Start Function
- Generator Compatible
- HID USB Communication




SNC-A Series 1500VA-3000VA

LINE INTERACTIVE RACK MOUNT UPS
-SINGLE PHASE

SNC-A Series 1500VA-3000VA Front and Rear Panels

- | | |
|---------------------------|-----------------------|
| 1. Power Button | 7. Intelligent Slot |
| 2. LCD Display | 8. RJ 11 / RJ 45 Port |
| 3. Set Up Button | 9. Ventilation Fan |
| 4. Overcurrent Protection | 10. EPO |
| 5. AC Input | 11. HID Enabled USB |
| 6. (3) BS 1363A | 12. RS-232 Port |



SNC-A Series 1500VA-3000VA

CE RoHS

SNC-A SERIES

Technical Specification

MODEL	SNC-A1500R	SNC-A2200R	SNC-A3000R
Capacity	1500VA / 900W	2200VA / 1540W	3000VA / 2100W
INPUT			
Nominal Voltage	220 - 240 VAC		
Voltage Range	165 - 290 VAC		
Frequency	50 / 60Hz (Auto sensing)		
OUTPUT			
Nominal Voltage (Battery Mode)	220 - 240 VAC		
Frequency (Battery Mode)	50Hz / 60Hz ± 1%		
Total Harmonic Voltage Distortion (THDv)	≤ 3% @ linear load, ≤ 5% @ non-linear load		
Ouput Connections	(3) BS 1363A		
TOPOLOGY			
Transfer Time	4 ms (Typical)		
Waveform (Battery Mode)	Pure Sinewave		
BATTERIES			
Battery Voltage	24V		
Battery Type	12V 7AH	12V 9AH	12V 7AH
Typical Recharge Time	4 hours recover to 90% capacity		
Charging Current	1A	2A	
SYSTEM			
LCD Display	Input Voltage, Output Voltage, Battery Percentage, Load Percentage and Faults		
Audible Alarm	Battery, Mode, Low Battery, Overload, Fault etc.		
SAFETY			
Overload Protection	On Utility: Circuit Breaker On Battery: Internal Firmware Protection		
RJ11 / RJ45 Surge Protection	Yes		
INTERFACE			
RS232	Yes		
HID Compliant USB Port	Yes		
SNMP	Yes		
EPO	Yes		
COMMUNICATIONS / MANAGEMENT			
Auto Recharge	Yes		
Auto Restart	Yes		
Power Management Software	Windows 2000 / XP / 7 / 8 / 10 / Server 2003 / Vista / Server 2008		
STANDARDS / APPROVALS			
Compliances	CE, RoHS		
IP Rating	IP 20		
ENVIRONMENT			
Operating Humidity	0% - 90% (non-condensing)		
Operating Temperature	0°C - 40°C		
PHYSICAL PROPERTIES			
Dimension (W x D x H) mm	438 x 430 x 88		
Net Weight (kg)	14.68	16.47	21.78
WARRANTY & SUPPORT			
Product Warranty	3 Years Full Warranty For Parts and Labour. 2 Years For Batteries.		

- Changes to the specification contained in this document, and to prices are reserved; so are errors and omissions.
- Only order confirmations and technical documentation by KOSS UPS is binding.
- Ver1.Jan 2024
- © POWER LOGIC (M) SDN BHD. All right reserved.



LINE INTERACTIVE RACK MOUNT UPS
-SINGLE PHASE



POWER LOGIC

No. 2-10, Jalan Kenari 12B, Bandar Puchong Jaya, 47100 Puchong, Selangor Darul Ehsan. Tel: (603) 8070 5899 E-mail: enquiry@kossups.com.my